

# Inductive Sensor with Increased Switching Distance

## IB120NM65VA3



Part Number



### Technical Data

Inductive Data	
Switching Distance	12 mm
Correction Factors V2A/CuZn/Al	1,05/0,46/0,43
Mounting	non-flush
Mounting A/B/C/D in mm	18/45/36/12
Switching Hysteresis	< 10 %
Electrical Data	
Supply Voltage	10...30 V DC
Current Consumption (U <sub>b</sub> = 24 V)	< 16 mA
Switching Frequency	380 Hz
Temperature Drift	< 10 %
Temperature Range	-40...80 °C
Switching Output Voltage Drop	< 2,5 V
PNP Switching Output/Switching Current	100 mA
Residual Current Switching Output	< 100 µA
Short Circuit Protection	yes
Reverse Polarity and Overload Protection	yes
Protection Class	III
Mechanical Data	
Housing Material	CuZn, nickel-plated
Full Encapsulation	yes
Degree of Protection	IP67
Connection	M12 × 1; 4-pin
Stock Type	●
PNP NO/NC antivalent	●
Connection Diagram No.	101
Suitable Connection Technology No.	2
Suitable Mounting Technology No.	170





Legend		
+	Supply Voltage +	nc not connected
-	Supply Voltage 0 V	U Test Input
~	Supply Voltage (AC Voltage)	Ū Test Input inverted
A	Switching Output (NO)	W Trigger Input
Ā	Switching Output (NC)	O Analog Output
V	Contamination/Error Output (NO)	O- Ground for the Analog Output
∇	Contamination/Error Output (NC)	BZ Block Discharge
E	Input (analog or digital)	AWV Valve Output
T	Teach Input	a Valve Control Output +
Z	Time Delay (activation)	b Valve Control Output 0 V
S	Shielding	SY Synchronization
RxD	Interface Receive Path	E+ Receiver-Line
TxD	Interface Send Path	S+ Emitter-Line
RDY	Ready	≡ Grounding
GND	Ground	SnR Switching Distance Reduction
CL	Clock	Rx+/- Ethernet Receive Path
E/A	Output/Input programmable	Tx+/- Ethernet Send Path
	IO-Link	Bus Interfaces-Bus A(+)/B(-)
PoE	Power over Ethernet	La Emitted Light disengageable
IN	Safety Input	Mag Magnet activation
OSSD	Safety Output	RES Input confirmation
Signal	Signal Output	EDM Contactor Monitoring

Wire Colors according to DIN IEC 757	
BK	Black
BN	Brown
RD	Red
OG	Orange
YE	Yellow
GN	Green
BU	Blue
VT	Violet
GY	Grey
WH	White
PK	Pink
GNYE	Green Yellow

## Mounting

